

SV-1 Specifications

HEAD DIAMETER -----	1-7/8" (47.6mm)
HEAD LENGTH-----	19" (482.6mm)
HEAD WEIGHT-----	11lbs. (5.0kg)
NO LOAD AMPERAGE: COMPLETE HEAD	
SV-1(115V) -----	2
SV-1(230V) -----	1
NO LOAD AMPERAGE: MOTOR ONLY	
SV-1(115V) -----	1
SV-1(230V) -----	.7
CENTRIFUGAL FORCE -----	800lbs. (3559N)
AMPLITUDE-----	.082" (2.08mm)
DIAMETER OF INFLUENCE-----	12"-16" (304.8mm-406.4mm)
WEIGHT OF COMPLETE UNIT-----	41lbs. (18.6kg)
POWER REQUIREMENTS	
SV-1(115V) -----	115V 3ph 180cy
SV-1(230V) -----	230V 3ph 180cy
RECOMMENDED POWER SOURCE	
SV-1(115V) -----	HHA-4C
SV-1(230V) -----	MHA-2C



*Specifications are nominal values and will vary depending on the size and range of aggregate, and the slump of the concrete.
Specifications taken at 10,500VPM.*

277 North Main Street
PO Box 367
Mansfield, OH 44902

www.minnich-mfg.com
e-mail: sales@minnich-mfg.com

Phone: 419.524.1000
Toll Free: 800.524.1033
Fax: 419.524.4000